

Network Video Recorder with PoE
H.265 compression



PoE ports



HD IPC



Network



CMS



STD

Key Features

- Support 4 / 8 CH 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-mode recording: manual / timer / motion / sensor
- Playback : 4 / 8 CH simultaneous playback
- Search : time slice, time, event (manual, sensor, motion), tag search
- Express and flexible backup via USB, network and so on
- Pentaplex : preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- 4 / 8 PoE network ports, support IPC direct connection to NVR; support PoE power supply
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log view and device status view
- 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with iOS and Andriod OS

Specification		VT-N1304HC-4P	VT-N1308HV-8P
System	Compression	Standard H.265 High Profile	
	OS	Embedded Linux	
Video	Network Input	4 Ch. IPC input	8 Ch. IPC input
	Access Bandwidth	40Mbps	50Mbps
	Network Access Format	5MP / 4MP / 3MP / 1080P / 960P / 720P@25 / 30fps	
	Output	HDMI (1080P) × 1 : 1920 × 1080	
Audio	Network Input	4 Ch. IPC audio	8 Ch. IPC audio
	Output	RCA × 1	
Record	Record Stream	Dual stream recording	
	Resolution	5MP / 4MP / 3MP / 1080P / 960P / 720P	
	Mode	Manual, timer, motion	
Playback	Simultaneous Playback	max. 4 CH	max. 8 CH
	Search	Time slice / time / event / tag search	
	Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events	
	Function	Play, pause, FF, FB, digital zoom, etc.	
Alarm	Mode	Manual, motion, exception	
	Input	4 CH IPC alarm input	8 CH IPC alarm input
	Output	No	
	Triggering	Record, snap, preset, e-mail, etc.	
Network	Interface	RJ45 10/100Mbps × 1	
	PoE Port	10/100 Mbps - Rj45 × 4	10/100 Mbps - Rj45 × 8
	Protocol	TCP/IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP	
	Web Client	Multiple users online	
Mobile Device	OS	iOS, Andriod	
Storage	HDD	SATA × 1, max. 6 T	
Backup	Local Backup	U disk, USB removable HDD	
	Network Backup	Yes	
Port	USB	USB 2.0 × 2 (one in the front panel and the other in the rear panel)	
	Remote Cont.	Optional (Remote Controller)	
Others	Power Supply	DC48V	
	Consumption	≤ 5W (without HDD and PoE)	≤ 5W (without HDD and PoE)
	Dimensions	300 x 248 x 52 (W x D x H) mm	
	Work Temp.	Work Environment -10 ~ 50°C, 10% ~ 90% humidity	

Design and specifications are subject to change without notice.

Dimensions

