

DHI-NVR4208/4216/4232-4KS2

8/16/32 Channel 1U 4K & H.265 Lite Network Video Recorder



- 8/16/32-channel IP video access
- Smart H.265+/Smart H.264+/H.265/H.264; H.265 auto switch
- Max 200 Mbps incoming bandwidth
- Up to 8MP resolution for preview and playback
- 8-channel decoding@1080p (30 fps)
- Al by Camera: Perimeter protection; SMD Plus; people counting; heat map



Dahua's new NVR4000-4KS2 network video recorder delivers excellent performance and high recording quality that is ideally suitable for IP video surveillance applications. This professional NVR adopts powerful processor, providing the capability of 4K resolution processing for applications where image details are highly required. Additionally, the NVR can be served as edge storage, central storage or backup storage with an intuitive shortcut operation menu for remote management and control.

System Overview

The NVR is compatible with numerous third-party devices, which make it the perfect solution for surveillance systems that work independently of video management system (VMS). It features an open architecture that supports multi-user access and is compatible with ONVIF 2.4 protocol, enabling interoperability with 4K cameras.

Functions

Perimeter Protection by Camera

Automatically filters out false alarms caused by animals, rustling leaves, bright lights, and more. Enables system to act secondary recognition for the targets. Improving alarm accuracy.

SMD Plus by Camera

With intelligent algorithm, Dahua smart motion detection technology can categorize the targets that trigger motion detection and filter the motion detection alarm triggered by non-concerned targets to realize effective and accurate alarm.

People Counting by Camera

With deep learning algorithm, Dahua People Counting technology can track and process moving human body targets to realize the accurate statistics of enter No., leave No., and In Area No. Working with management platform, it outputs yearly/monthly/weekly/daily reports to meet your requirements.

Smart Codec

With advanced scene-adaptive rate control algorithm, Dahua smart codec technology realizes the higher encoding efficiency than H.265 and H.264, provides high-quality video, and reduces the cost of storage and transmission.

ANR (Automatic Network Replenishment Technology)

Video record in SD card in IP cameras when the network breaks down, and after the network recovered, the video will be transferred to device and then recorded in it.

DMSS

The DMSS app is available on the iOS App Store and Google Play. It makes surveillance easy and simple, allowing you to remotely access back-end devices, view live video, receive event push notifications, and search for recorded videos from an iPhone, iPad, or Android phone at anytime from virtually anywhere.

Pro Series | DHI-NVR4208/4216/4232-4KS2

Technical Specification


Technical Specification			
System			
Main Processor	Industrial embedded micro-processor		
Operating System	Embedded Linux		
Operation Interface	Web; local GUI		
Perimeter Protection by Camera			
Performance	8/16/32 channels		
AI Search	Search for pictures by channel, time and event type		
SMD Plus by Camera			
Performance	8/16/32 channels		
AI Search	Search by target classification (human, vehicle)		
Video			
Access Channel	8/16/32		
Network Bandwidth	200 Mbps for access, 200 Mbps for storage and 96 Mbps for forwarding		
Resolution	8MP, 6MP, 5MP, 4MP, 3MP, 1080p, 1.3MP, 720p, D1, and more		
Decoding Capability	8 channels@1080p (30 fps)		
Video Output	HDMI: 3840 × 2160; 1920 × 1080; 1280 × 1024; 1280 × 720 VGA: 1920 × 1080; 1280 × 1024; 1280 × 720		
Multi-screen Display	8-channel: 1/4/8/9 16-channel: 1/4/8/9/16 32-channel: 1/4/8/9/16/25/36		
Third Party Camera Access	Panasonic, Sony, Samsung, Axis, Pelco, Arecont, ONVIF, Canon and more		
Compression			
Video	Smart H.265+; Smart H.264+; H.265; H.264		
Audio	PCM; G.711A; G.711U; G.726		
Network			
Network Protocol	HTTP; HTTPS; TCP/IP; IPv4/IPv6; UPnP; SNMP; RTSP; UDP; SMTP; NTP; DHCP; DNS; IP Filter; DDNS; FTP; Alarm Server; IP Search (supports Dahua IP camera, DVR, NVS, and more); P2P		
Mobile Phone Access	Android; iOS		
Interoperability	ONVIF (profile T/S/G); CGI; SDK		
Browser	Chrome; IE9 or later; Firefox		
Record Playback			
Multi-channel Playback	8-channel: 1/4/9 16/32-channel: 1/4/8/9/16		
Record Mode	Manual; schedule (general; MD; alarm; MD & alarm; intelligent)		
Storage Method	Local HDD and network		
Backup	USB device		
Playback Function	1. Play; pause; stop; fast forward; fast backward; rewind; play by frame 2. Full screen; backup (cut/file) ; partially enlarge; audio on/off		


Disk GroupYesAlarmMotion detection; privacy masking; video loss; f alarm; IPC alarmGeneral AlarmMotion detection; privacy masking; video loss; f alarm; IPC alarmAnomaly AlarmCamera offline; storage error; full storage; IP conflict; MAC conflict; login lock; network secur anomalyIntelligent AlarmPerimeter protection; SMD; people counting; he mapAlarm LinkageRecord; snapshot; IPC external alarm output; buzzer; log; preset; emailExternal PortAudio InputAudio Output1 channel, RCA connector, which support voice intercom outputHDD2 SATA III ports, up to 10 TB for a single HDD. Th maximum HDD capacity varies with environmer temperatureAlarm Input4 channelsAlarm Output2 channels	ty	
General AlarmMotion detection; privacy masking; video loss; f alarm; IPC alarmAnomaly AlarmCamera offline; storage error; full storage; IP conflict; MAC conflict; login lock; network secur anomalyIntelligent AlarmPerimeter protection; SMD; people counting; he mapAlarm LinkageRecord; snapshot; IPC external alarm output; buzzer; log; preset; emailExternal PortI channel, RCA connectorAudio Input1 channel, RCA connector, which support voice intercom outputHDD2 SATA III ports, up to 10 TB for a single HDD. Th maximum HDD capacity varies with environment temperatureAlarm Input4 channels	ty	
General Alarmalarm; IPC alarmAnomaly AlarmCamera offline; storage error; full storage; IP conflict; MAC conflict; login lock; network secur anomalyIntelligent AlarmPerimeter protection; SMD; people counting; he mapAlarm LinkageRecord; snapshot; IPC external alarm output; buzzer; log; preset; emailExternal Port1 channel, RCA connectorAudio Input1 channel, RCA connector, which support voice intercom outputHDD2 SATA III ports, up to 10 TB for a single HDD. Th maximum HDD capacity varies with environment temperatureAlarm Input4 channels	ty	
Anomaly Alarmconflict; MAC conflict; login lock; network secur anomalyIntelligent AlarmPerimeter protection; SMD; people counting; he mapAlarm LinkageRecord; snapshot; IPC external alarm output; buzzer; log; preset; emailExternal PortI channel, RCA connectorAudio Input1 channel, RCA connectorAudio Output1 channel, RCA connector, which support voice intercom outputHDD2 SATA III ports, up to 10 TB for a single HDD. Th maximum HDD capacity varies with environment temperatureAlarm Input4 channels		
Intelligent Alarm map Alarm Linkage Record; snapshot; IPC external alarm output; buzzer; log; preset; email External Port Audio Input Audio Input 1 channel, RCA connector Audio Output 1 channel, RCA connector, which support voice intercom output HDD 2 SATA III ports, up to 10 TB for a single HDD. Th maximum HDD capacity varies with environment temperature Alarm Input 4 channels	at	
Alarm Linkage buzzer; log; preset; email External Port Audio Input 1 channel, RCA connector Audio Output 1 channel, RCA connector, which support voice intercom output HDD 2 SATA III ports, up to 10 TB for a single HDD. Th maximum HDD capacity varies with environmer temperature Alarm Input 4 channels		
Audio Input 1 channel, RCA connector Audio Output 1 channel, RCA connector, which support voice intercom output HDD 2 SATA III ports, up to 10 TB for a single HDD. Th maximum HDD capacity varies with environment temperature Alarm Input 4 channels		
Audio Output 1 channel, RCA connector, which support voice intercom output HDD 2 SATA III ports, up to 10 TB for a single HDD. Th maximum HDD capacity varies with environment temperature Alarm Input 4 channels		
Addio Output intercom output HDD 2 SATA III ports, up to 10 TB for a single HDD. Th maximum HDD capacity varies with environmer temperature Alarm Input 4 channels		
HDD maximum HDD capacity varies with environmentemperature Alarm Input 4 channels		
Alarm Output 2 channels		
USB 1 front USB 2.0 port, 1 rear USB 3.0 port		
HDMI 1		
VGA 1		
Network 1 RJ-45 10/100/1000 Mbps self-adaptive Etherr port	et	
General Parameter		
Power Supply 12V/4A DC		
Power Consumption < 6.9 W (without HDD)		
Net Weight 1.6 kg (3.5 lb) (without HDD)		
Gross Weight 3.2 kg (7.1 lb) (without HDD)		
Product Dimensions 375.0 mm × 282.4 mm × 53.0 mm (14.8" × 11.1" 2.1")	~	
Package Dimensions 429 mm × 360 mm × 137 mm (16.9" × 14.2" × 5.40 mm × 137 mm (16.9" × 14.2" × 5.40 mm × 137 mm (16.9" × 14.2" × 5.40 mm × 137 mm (16.9" × 14.2" × 5.40 mm × 137 mm (16.9" × 14.2" × 5.40 mm × 137 mm (16.9" × 14.2" × 5.40 mm × 137 mm (16.9" × 14.2" × 5.40 mm × 137 mm (16.9" × 14.2" × 5.40 mm × 137 mm (16.9" × 14.2" × 5.40 mm × 137 mm (16.9" × 14.2" × 5.40 mm × 137 mm (16.9" × 14.2" × 5.40 mm × 137 mm (16.9" × 14.2" × 5.40 mm × 137 mm (16.9" × 14.2" × 5.40 mm × 140 mm	·")	
Operating Temperature -10°C to +55°C (+14°F to +131°F)	-10°C to +55°C (+14°F to +131°F)	
Storage Temperature 0°C to +40°C (+32°F to +104°F)		
Operating Humidity 10%–93% (RH)		
Storage Humidity 30%–85% (RH)		
Operating Altitude 3,000 m (9,843 ft)		
CE: EN55032; EN55024; EN50130-4; EN60950-1 FCC: Part 15 Subpart B; ANSI C63.4-2014 UL: UL 60950-1		

Pro Series | DHI-NVR4208/4216/4232-4KS2


Ordering Information		
Туре	Model	Description
8 Channel NVR	DHI-NVR4208-4KS2	8 Channel 1U 4K & H.265 Lite Network Video Recorder
16 Channel NVR	DHI-NVR4216-4KS2	16 Channel 1U 4K & H.265 Lite Network Video Recorder
32 Channel NVR	DHI-NVR4232-4KS2	32 Channel 1U 4K & H.265 Lite Network Video Recorder

Dimensions (mm[inch])





Panels



Rev 001.001 © 2020 Dahua. All rights reserved. Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.