

- Eficienta ridicata de conversie a modulelor
- Reduce degradarea puterii
- Performanta optimizata in conditii de lumina scazuta
- Cutia de jonctiune clasificată IP67, cablurile fiabile și conectorii standard MC4 îmbunătățesc stabilitatea

SZ-180-36M

Mechanical Data	
Standard Test Conditions AM=1.5, E=1000W/m ² , TC=25°C	
Nominal Power	180W
Cell Type/Efficiency	Monocrystalline / 21.20%
Cell Arrangement	36 (4*9)
Maximum Power Current (I _{mpp})	9.89A
Maximum Power Voltage (V _{mpp})	18.20V
Open-circuit Voltage (V _{oc})	21.50V
Short-circuit Current (I _{sc})	10.41A
Maximum System Voltage	1000V
Output Tolerance	+3%
Cable	750mm / 2.5mm ²
Connector Type	MC4 / MC4 Compatible
Module Structure	Aluminum Frame / Glass / EVA / Backsheet (White)
Junction box rating	≥ IP67
Number of Diodes	Two
Working Temperature	-40°C ~ +80°C
Packaging	
Module Dimensions	1480*670*35mm
Module Weight	11.83kg
Package	Single Package
Pieces per Pallet	26
Gross Weight per Pallet	330kg
Pallet Dimensions	1540*1100*1000mm