


<b>Picture</b>		
<b>Model</b>	<b>E Series E340</b>	
<b>Video &amp; Audio</b>	Image Sensor	1/2.7" CMOS Sensor
	Video Resolution	2560x1920 (5MP)@15FPS
	Lens	f=2.8mm-4mm, F=2.0
	Video Format	H.264
	Field of View	Horizontal: 98°- 48°
		Vertical:75°- 37°
	Day & Night	IR-cut filter with auto-switching
	Infrared Night Vision	Up to 12 Meters (40ft)(LED: 10pcs/14mil/850nm)
<b>Power</b>	DC Power	DC 5V=2A
<b>Interface</b>	Power	DC power port
	System	Reset Button
	Ethernet	One 10M/100Mbps RJ45
	Storage	MicroSD card slot (Max. 256GB)
	Audio	Built-in Microphone and Speaker
<b>Pan&amp;Tilt</b>	Pan &Tilt Range	Pan: 355°, Tilt: 0°~50°
	Auto Tracking	Support
<b>Wi-Fi</b>	Wireless Standard	IEEE 802.11 a/b/g/n
	Operating Frequency	2.4 GHz/5 GHz
	Wireless Security	WPA-PSK/WPA2-PSK
<b>Software Features</b>	Frame Rate	Main Stream: 2fps - 20fps(default: 20fps)
		Sub Stream: 4fps - 15fps(default: 7fps)
	Code Rate	Main Stream: 1024Kbps -5120Kbps(default: 4096Kbps)
		Sub Stream: 128Kbps -512Kbps(default: 160Kbps)
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Smart Alarm	Motion detection/Human Detection/Pet Detection
	Record Mode	Motion Record/Schedule Record (Default: Motion Record)
	Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
Maximal User Access	Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams); 20 Users (1 admin account & 19 user accounts)	
<b>Working Environment</b>	Temperature	Operating Temperature: -10°C~+55°C (14°F~131°F)
	Humidity	Operating Humidity: 20% ~ 85%
<b>Size &amp; Weight</b>	Dimension	Φ84x118mm
	Weight	275g
<b>Warranty</b>	Limited Warranty	2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a>