

# 27 inches IT Monitor

MW-LC27-E



## Features


- Resolution is up to at 1920 x 1080.
- Refresh rate up to 100 Hz.
- 178 horizontal and vertical viewing angle.
- Screen can reduce blue light, protect eyes.
- Plastic body, ultra-narrow bezel, light weight and elegant.
- Shielding cover design, effectively preventing electromagnetic radiation.
- Stable structure design, highly durable.
- Automatically detect if the signal is connected successful.
- Support multiple language.

## Specifications


Panel	Description
Backlight	LED
Panel Size	27"
Pixel Pitch (H x V) (mm)	0.31 x 0.31
Resolution	1920 x 1080
Color Support	16.7 M

Brightness (cd/m <sup>2</sup> )	250
Contrast Ratio	4000:1
Refresh Rate	100 Hz
Response Time (ms)	5
Viewing Angle (H/V)	Horizontal 178°, Vertical 178°
Display Size (mm)	597.9 x 336.8
Operation Hour	18/7
<b>Interface</b>	Description
Video Input	1 x HDMI(1920 x 1080@100 HZ), 1 x VGA(1920 x 1080@60 HZ)
<b>VESA</b>	Description
VESA (mm)	75 x 75
Wall-mounted Thread	4-M4 Threaded Hole, 8mm Deep Thread
<b>OSD</b>	Description
Multi-Language	Chinese, English, German, French, Italian, Spanish, Portuguese, Turkish, Polish, Dutch, Japanese, Korean
<b>General</b>	Description
Input Voltage	DC 12 V, 3 A
Typical Power Consumption (W)	≤36
Standby Power Consumption (W)	≤0.5
Package Dimensions (W x H x D) (mm)	694 x 458 x 114
Weight (Kg)	Net Weight: 3.84 Gross Weight: 5.25
Operating Temperature	0°C ~ 40°C
Operating Humidity	10% ~ 85% (No Condensation)
Storage Temperature	-20°C ~ 60°C
Storage Humidity	5% ~ 90% (No Condensation)
Standard	1 x HDMI Cable, 1 x Quick Guide, 1 x Pedestal, 1 x Adapter

## Dimensions



## Interface



## Ordering Info

Product Model	Description
MW-LC27-E	27 inches IT Monitor

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)

<http://www.uniview.com>

©2024 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.