

THC-T120-P 2 MP Indoor Fixed Turret Camera



- 1080p turret camera
- Smart IR: up to 20 m IR distance
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).

▪ Specification





Camera	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.01 Lux@(F2.0, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 75°, Rotation: 0° to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm, 3.6 mm and 6 mm fixed focal lens
Focal Length & FOV	2.8 mm, horizontal FOV: 103 3.6 mm, horizontal FOV: 80.7 6 mm, horizontal FOV: 50.1
Lens Mount	M12
Illuminator	
Supplement Light Type	IR
Supplement Light Range	Up to 20 m
Image	
Image Settings	Brightness, Mirror, Smart IR, Sharpness, AGC
Frame Rate	PAL: 1080p@25fps NTSC: 1080p@30fps
Day/Night Mode	Auto/Color/BW (Black and White)
Image Enhancement	DWDR, BLC
Noise Reduction	2D DNR
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS, 1 HD analog output
General	
Power	12 VDC ±15%, max. 4 W
Material	Plastic
Dimension	∅ 85.4 mm × 76.12 mm (∅ 3.38" × 2.67")
Weight	Approx. 130 g (0.29 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensation)
Language	English

▪ Available Model

THC-T120-P

- **Accessory**

- **Optional**

HIA-J101 Junction Box	HIA-B201 Corner Mount	HIA-B301 Vertical Pole Mount	HIA-B401-110T Wall Mount
			

HiLook

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
Technical Support: support@hikvision.com

Follow us on social media to get the latest product and solution information.

