



Reolink Innovation Limited

Model	NVS4	
Video/Audio Input	IP Video Input	Up to 4 IP cameras
	Audio Input	N/A
Video/Audio Output	Video Output	VGA, HDMI
	Display Resolution	• HDMI: 3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768 • VGA: 1920x1080, 1280x1024, 1280x720, 1024x768
	Audio Output	1CH RCA(add on Speaker)
	Video Compression	H.264/H.265
Decoding	Live View/Playback Resolution	7680x2160, 4608X1728,4512X2512,4096X3072,3840X2160, 2560X2560, 2560X1920, 2560X1440,2048X1536, 2304X1296,1080P, 720P
	Synchronous Playback	Up to 4 channels
	HDD	SATA
HDD	Capacity	Up to 6TB
	External Interface	USB Interface
External Interface	Network Interface	4 x RJ-45, 10/100 Mbps self-adaptive (for IP cameras) 1 x RJ-45, 10/100 Mbps self-adaptive (for LAN/WAN)
	PoE	Max. Power per Port
PoE	Supported Standard	IEEE 802.3af/at
	Network	Network Protocols
Browsers Supported		Edge, Firefox, Chrome, Safari
OS Supported		PC: Windows, Mac OS; smartphone: iOS, Android
User Access		Max. 20 users (1 admin & 19 user); Max. 12 simultaneous streams (10 sub & 2 mainstreams)
General	Power Supply	DC 52V
	Power Consumption	<10W (without HDD&PoE)
	Working Environment	Temperature: -10°C ~ +45°C (14°F ~ 113°F); Humidity: 10% ~ 90%
	Dimensions	255mm(W) x 495mm(H) x 232mm(D)
	Weight	1.4kg
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .

