

Picture



Model

TrackMix Series G770

Video & Audio

| | |
|-----------------------|---|
| Image Sensor | 1/3"+1/2.7"CMOS Sensor |
| Video Resolution | UP To: 3840 x 2160 (4.0 Megapixels) at 15 frames/sec |
| Lens | f=2.8mm@F=1.6, f=8mm@F=1.6 |
| Video Format | H.264,H.265 |
| Field of View | Horizontal: 108°-57° Vertical: 38°-21° |
| Zoom Mode | 6X hybrid zoom |
| Day & Night | IR-cut filter with auto-switching |
| Infrared Night Vision | Up to 30 Meters (90ft)(LED: 2pcs/850nm) |
| Color Night Vision | Spotlight: 1pcs/6500K/450 Lumens |
| Frame Rate | Main Stream: 10fps - 15fps(Default: 15fps) Sub Stream: 10fps - 15fps |
| Code Rate | Main Stream: 1024Kbps - 4096Kbps(Default:3072Kbps) Sub Stream: 64Kbps -672Kbps |
| Audio | Two-way Audio |

Power Requirements

| | |
|----------|--|
| Battery | 7.2V,5100mAh (36.72Wh) rechargeable battery (Battery life varies based on settings, usage & temperature) |
| Solar | Reolink Solar Panel 2 |
| DC Power | 5V/2A |

Interface

| | |
|---------------|---------------------------------|
| Power Power | USB Type-C port |
| Reset Button | Yes |
| SD Card Slot | MicroSD card slot (Max. 128GB) |
| SIM Card Slot | Nano SIM card slot |
| Audio In/Out | Built-in Microphone and Speaker |

Pan&Tilt

| | |
|---------------|--|
| Pan &Tilt | Pan: 355°, Tilt: 0°-90°; (PT speed is configurable) |
| Preset Points | Suppots 1 guard position & up to 32 preset positions |
| Auto-Tracking | Support |

3G/4G

| | |
|-----------------|--|
| Frequency Bands | Europe: LTE FDD: B1/B3/B7/B8/B20/B28A WCDMA: B1/B8 |
| | America: LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71 |
| | Australia: LTE FDD: B1/B3/B5/B7/B8/B28 WCDMA: B1/B5/B8 |

Software

| | |
|-----------------------|---|
| OS Supported | PC: Windows, Mac OS; Smartphone: iOS, Android |
| Protocols & Standards | SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P |
| User Access | Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams) |

Other Features

| | |
|--------------------------|--|
| Smart Alarm | PIR Detection/Human Detection/Vehicle Detection/Animal Detection |
| PIR Detecting Distance | Adjustable, up to 11m (33ft) |
| PIR Detecting Angle | 100° horizontal |
| Record Mode | Motion Triggered Recording |
| Time Lapse | Yes |
| Smart Home Compatibility | Google Assistant |
| Cloud Storage | Supports Reolink Cloud (available in selected countries) |

Working Environment

| | |
|--------------|---|
| Temperature | Operating Temperature: -10°C~+55°C (14°F~131°F) |
| Humidity | Operating Humidity: 20% ~ 85% |
| Weatherproof | IP65 |

Mechanical

| | |
|-----------|-----------------|
| Dimension | 228.2*147*129mm |
| Weight | 1.4KG |

Warranty

| | |
|------------------|---|
| Limited Warranty | 2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ |
|------------------|---|