

IPC-F120-LIDF/W 2 MP Indoor Wi-Fi Fixed PT Turret



HiLook IPC-F120-LIDF/W 2 MP PT Network Camera is ideal for indoor HD monitoring in small businesses and offices and for close range monitoring in warehouses, lobbies, server rooms, garages, etc.

- High quality imaging with 2 MP resolution
- Digital WDR, HLC, BLC, 3D DNR
- Support Wi-Fi 6
- Good night-time performance with up to 20 m IR and 15 m white light
- Built-in microphone and speaker, support two-way audio

• Specification

Camera	
Image Sensor	1/3" Progressive Scan CMOS
Max. Resolution	1920 × 1080
Min. Illumination	Color: 0.03 Lux @ (F2.2, AGC ON), B/W: 0.015Lux @(F2.2, AGC ON), 0 Lux with IR
Lens	
Focal Length	2.8 mm, 4 mm
FOV	2.8 mm: Horizontal FOV 96.5°, vertical FOV 52.3°, diagonal FOV 115.7°, 4 mm: Horizontal FOV 76.8°, vertical FOV 42.5°, diagonal FOV 89.7°
Aperture	F2.2
Illuminator	
Supplement Light Type	IR, White Light
Supplement Light Range	White light distance: up to 15 m, IR distance: up to 20 m
IR Wavelength	850 nm
PTZ	
Movement Range (Pan)	0° to 350°
Movement Range (Tilt)	0° to 75°
Pan Speed	Up to 20°/s
Tilt Speed	Up to 10°/s
Video	
Main Stream	50 Hz: 25 fps (1920 × 1080, 1280 × 720) 60 Hz: 30 fps (1920 × 1080, 1280 × 720)
Sub-Stream	50 Hz: 25 fps (768 × 432) 60 Hz: 30 fps (768 × 432)
Video Compression	H.265, H.264, MJPEG
Video Bit Rate	32 Kbps to 8 Mbps
H.264 Type	Baseline Profile/Main Profile/High Profile
H.265 Type	Main Profile
Audio	
Audio Compression	G.711ulaw/AAC-LC
Audio Bit Rate	AAC-LC: 16 Kbps, 32 Kbps, 64 Kbps; G.711ulaw: 64 Kbps
Audio Sampling Rate	8 kHz/16 kHz
Environment Noise Filtering	Yes
Network	
Protocols	IPv4/IPv6, HTTP, QoS, SMTP, NTP, RTSP, RTP, RTCP, TCP/IP, UDP, DHCP, Bonjour
API	Open Network Video Interface (Profile S, Profile G, Profile T), ISAPI, SDK, Hik-Connect
Wireless (Wi-Fi)	
Wi-Fi Protocols	IEEE802.11b, IEEE802.11g, IEEE802.11n, IEEE802.11ax
Frequency Range	2.4 GHz to 2.4835 GHz
Channel Bandwidth	20/40 MHz
Wireless Range	Up to 80 m (The performance varies based on actual environment)
Image	
Image Settings	Saturation, brightness, contrast, and sharpness adjustable by client software or web browser
Wide Dynamic Range (WDR)	Digital WDR

Image Enhancement	BLC, HLC, 3D DNR
Interface	
Ethernet Interface	1 RJ45 10M/100M self-adaptive Ethernet port
Built-in Microphone	1 built-in microphone
On-board Storage	Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB
Built-in Speaker	1 built-in speaker
Event	
Basic Event	Motion detection (support alarm triggering by specified target types (human and vehicle)),video tampering alarm,exception
Linkage	notify surveillance center, send email, trigger recording (-F) , trigger capture, audible warning
General	
Power	12 VDC $\pm$ 25%, reverse polarity protection, 0.75 A, max. 9 W, $\varnothing$ 5.5 mm coaxial power plug
Dimension	$\varnothing$ 124 mm $\times$ 119 mm ($\varnothing$ 4.89" $\times$ 4.68")
Weight	Weight:Approx. 290 g (0.6 lb.) With Package Weight:Approx. 390 g (0.8 lb.)
Material	Plastic
Operating Condition	-10 °C to 40 °C (-14 °F to 104 °F). Humidity 90% or less (non-condensing)
General Function	Heartbeat,anti-banding,mirror,password protection,password reset via email
Approval	
Protection	IP54
Network	
User/Host	Up to 32 users. 3 levels: Administrator, Operator and User
Security	Password protection, complicated password, watermark, basic and digest authentication for HTTP, WSSE and digest authentication for Open Network Video Interface, security audit log, host authentication (MAC address)
Client	Wired network: HiLookVision, iVMS-4200 Wi-Fi: iVMS-4200 *Wi-Fi connection with HiLookVision directly is not possible
Image	
Privacy Mask	4 programmable rectangle privacy masks
General	
Language	English, Ukrainian





▪ Available Model

IPC-F120-LIDF/W(2.8mm)(B)

IPC-F120-LIDF/W(4mm)(B)

IPC-F120-LIDF/W(2.8mm)(HIK POLAND)KIT

▪ Dimension



Unit: mm [inch]

SCALE	1:1
-------	-----

See Far, Go Further



www.hikvision.com
support@hikvision.com



© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HiLook